


**Identification**

CH<sub>3</sub>OH  
 M = 32,04 g/mol  
 CAS [67-56-1]  
 EC number: 200-659-6  
 Taric code: 2905 11 00


**Synonyms**

Methyl alcohol, Carbinol, Methynol, Wood alcohol

**Applications**

solvents, synthesis of organic products, in antifreeze compositions, solvent for animal and vegetable oils extractions.

**Specifications**

assay (G.C.).....	min. 99,9 %	indium (In).....	max. 0,02 ppm
identity (IR-spectrum).....	passes test	iron (Fe).....	max. 0,1 ppm
density (20°/20°).....	0,791 - 0,793	lead (Pb).....	max. 0,1 ppm
appearance.....	clear	lithium (Li).....	max. 0,02 ppm
colour (Hazen).....	max. 10	magnesium (Mg).....	max. 0,1 ppm
boiling point.....	64 - 65 °C	manganese (Mn).....	max. 0,02 ppm
solubility in water.....	passes test	molybdenum (Mo).....	max. 0,02 ppm
acidity.....	max. 0,0002 meq/g	nickel (Ni).....	max. 0,02 ppm
alkalinity.....	max. 0,0002 meq/g	platinum (Pt).....	max. 0,05 ppm
chlorides (Cl).....	max. 0,5 ppm	silver (Ag).....	max. 0,02 ppm
sulfates (SO <sub>4</sub> ).....	max. 1 ppm	thallium (Tl).....	max. 0,02 ppm
aluminium (Al).....	max. 0,5 ppm	tin (Sn).....	max. 0,1 ppm
arsenic (As).....	max. 0,02 ppm	titanium (Ti).....	max. 0,02 ppm
barium (Ba).....	max. 0,1 ppm	vanadium (V).....	max. 0,02 ppm
beryllium (Be).....	max. 0,02 ppm	zinc (Zn).....	max. 0,1 ppm
bismuth (Bi).....	max. 0,02 ppm	zirconium (Zr).....	max. 0,02 ppm
cadmium (Cd).....	max. 0,05 ppm	acetone (G.C.).....	max. 0,001 %
calcium (Ca).....	max. 0,5 ppm	formaldehyde (G.C.).....	max. 0,001 %
chromium (Cr).....	max. 0,02 ppm	acetaldehyde (G.C.).....	max. 0,001 %
cobalt (Co).....	max. 0,02 ppm	carbonyl compounds .....	max. 0,001 %
copper (Cu).....	max. 0,02 ppm	substances darkened by H <sub>2</sub> SO <sub>4</sub> .....	passes test
gallium (Ga).....	max. 0,02 ppm	substances reducing KMnO <sub>4</sub> .....	passes test
gold (Au).....	max. 0,02 ppm	residue on evaporation.....	max. 5 ppm
		water (K.F.).....	max. 0,05 %

**Physical data**

- Density: 0,792 g/cm<sup>3</sup>
- Solub. in water: (20 °C): miscible
- Melting point: -98 °C
- Boiling point: 65 °C
- Flash point: 10 °C
- Ignition temperature: 455 °C
- Vapour pressure: (20 °C) 128 hPa
- Refraction index: (n 20 °C/D) 1,3288
- Viscosity: (20 °C) 0,52 mPas
- Dipolar moment: (20 °C) 1,7 Debye
- Dielectric const.: (25 °C) 32,6
- Evap. heat: (65 °C) 1100 KJ/kg
- Saturation conc.: (20 °C) 166 g/m<sup>3</sup>
- Expl. limit (upper): 44 Vol%
- Expl. limit (lower): < 5,5 Vol%
- pH7
- Hygroscopic

**Safety - GHS****Signal Word:** Danger**Hazard Statements:**

H225: Highly flammable liquid and vapour.  
H301: Toxic if swallowed.  
H311: Toxic in contact with skin.  
H331: Toxic if inhaled.  
H370: Causes damage to organs.

**Precautionary Statements:**

P210: Keep away from heat / sparks / open flames / hot surfaces. - No smoking.  
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P303+P361+P353: IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.  
P370+P378: In case of fire: Use ... for extinction.  
P405: Store locked up.  
P501a: Dispose of contents / container in accordance with local / regional / national / international regulations.

**Transport/storage**

- ADR: 3 FT1 II • UN 1230 • METHANOL
- IMDG: 3 II • UN 1230 • METHANOL
- IATA/ICAO: 3 II • UN 1230 • METHANOL
- PAX: 352
- CAO: 364
- 10°C - 30°C