

Potassium hydroxide, 90%, flakes, EssentQ®**Identification**

KOH
M = 56,11 g/mol
CAS [1310-58-3]
EC number: 215-181-3
Taric code: 2815 20 10

Synonyms

Potash caustic, Potassium hydrate, Potassium oxide hydrate

Applications

analytical chemistry, laboratory reagent, titrant in volumetric analysis, synthesis of organic products, in the pharmaceuticals industry.

Specifications

assay (acidimetric).....	approx. 90 %	sulfates (SO ₄).....	max. 0,05 %
insoluble in water.....	max. 0,05 %	arsenic (As).....	max. 3 ppm
chlorides (Cl).....	max. 0,02 %	iron (Fe).....	max. 0,005 %
		lead (Pb).....	max. 0,005 %

Physical data

- Appearance: flakes, white or almost white, up to 2cm
- Spec. Density: 2,04 g/cm³
- Solub. in water: (20 °C): soluble
- Melting point: 360 °C
- Boiling point: 1320 °C
- pH(56 g/l H₂O, 20 °C) ~ 14
- Hygroscopic

Safety - GHS

Signal Word: Danger

Hazard Statements:

- H314: Causes severe skin burns and eye damage.
H302: Harmful if swallowed.

**Precautionary Statements:**

- P260: Do not breathe dust / fume / gas / mist / vapours / spray.
P303+P361+P353: IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor / physician.
P405: Store locked up.
P501a: Dispose of contents / container in accordance with local / regional / national / international regulations.

Transport/storage

- ADR: 8 C6 II • UN 1813 • POTASSIUM HYDROXIDE, SOLID
- IMDG: 8 II • UN 1813 • POTASSIUM HYDROXIDE, SOLID
- IATA/ICAO: 8 II • UN 1813 • POTASSIUM HYDROXIDE, SOLID
- PAX: 814
- CAO: 816
- 10°C - 30°C